



**725328 (RE4142FFR)**

2-door Freezer 1430lt, -22-15°C, digital, stainless steel, remote

## Main Features

- Automatic defrost
- Freezer model has operating temperatures that can be adjusted from -22 to -15 °C.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Right hinged full door.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m\*K).
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Internal structure with numerous charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Optimized back to front forced air flow provide even temperature distribution and fast cooling in any conditions.
- Equipped with single phase electrical cable and Schuko plug for easy and fast installation.
- Tropicalized unit

## Construction

- Lockable door.
- Mounted on adjustable Stainless steel feet, with castors as an option.
- The rounded internal corners, the easily removable runners and grids allow for ease of cleaning and high hygiene standards.
- Easy access to the main components for maintenance.
- Stainless steel runners and supports easily disassembled.
- Anti-corrosion bottom material avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Doors are self-closing and can be fully opened up to 180°.
- AISI 430 stainless steel internal structure and external panels.



## User Interface & Data Management

---

- Large digital white-digit display with cabinet temperature display and setting, activation of turbo frost cycle (to rapidly cool warm loads) and possibility to activate manually the defrost cycle.
- Easy serviceability thanks to the intuitive control panel with access via app.
- Integrated RS485 port to facilitate connection to a remote computer and integrated HACCP systems.





# A focus on sustainability

## Sustainability

- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.

## Certifications & Recognitions



International system for mutual acceptance of test reports and certificates concerning the safety of electrical and electronic components, equipment, and products.



Product assessed by the manufacturer and deemed to meet EU safety, health, and environmental protection requirements.



Find out more:  
[ISO Certificates](#)  
[Electrolux Professional Recognitions](#)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026/04/20

3/7

# Technical specifications

## Electric

Supply voltage:	220-240 V/1 ph/50/60 Hz
Electrical power max.:	0.21 kW

## Key Information:

Number and type of grids (included):	6 (GN 2/1)
External dimensions, Width:	1441 mm
External dimensions, Depth:	835 mm
External dimensions, Depth with Doors Open:	1480 mm
External dimensions, Height:	2050 mm
Number and type of doors:	2 Full
Type of external material:	Stainless Steel AISI 430
Type of internal material:	Stainless Steel AISI 430
Internal panels material:	Stainless Steel AISI 430
Number of positions & pitch:	44; 30 mm
Gross capacity:	1430 liter

## Refrigeration Data

Control type:	Digital
Refrigeration type:	
Suggested refrigeration power:	965 W
Suggested refrigeration power (second unit):	0 W
Condition at evaporation temperature:	-30 °C
Condition at condensation temperature:	55 °C
Condition at ambient temperature:	32 °C
Connection pipes (remote) - outlet:	9.5 mm
Connection pipes (remote) - inlet:	6 mm
*Note:	Ref. Power calculated at a linear distance of 15 mt (piping)

## ISO Certificates

ISO Standards:	ISO 9001; ISO 14001; ISO 45001; ISO 50001
Type reference/certification group:	V2MGBTR



# Accessories

## Included Accessories

PNC Code	Description	Quantity
881020	2/1GN grey rilsan grid with 2 runners	6

## Optional Accessories

PNC Code	Description
----------	-------------

### Baskets

881043	1/1GN rilsan steel wire basket h=150mm
--------	--

### Containers, trays and grids

880242	2 stainless steel runners for refrigerated cabinets - (Marine)
880243	Set of 8 GN1/1 PVC containers for fish
880248	Spacer for 670 lt and 1430 lt refrigerated cabinets
880333	Kit 20 pair runners and tray supports to fit pastry trays (400x600mm)
880705	1/1GN plastic container with false bottom
881004	2/1GN grey rilsan grid
881016	2/1GN aisi 304 stainless steel grid
881018	2/1GN 304 AISI stainless steel grid with 2 runners
881020	2/1GN grey rilsan grid with 2 runners
881021	Set of 2 stainless steel runners for 670/1430lt refrigerators and freezers
881039	2/1GN pvc container with lid and 2 runners
881042	2/1GN perforated shelf
881044	3 grey rilsan central grids for 1430lt (not for glass door)
881047	2/1GN grey rilsan basket+2 runners h=150mm

### Feet, wheels and ramps

881033	Pedal opening for 1430lt refrigerator
881294	5 swivelling wheels (2 with brake), diam 125mm, for 1430 lt refrigerators, NOT for remote models

### Remote units

880233	Remote unit -22-15°C for 1430lt refrigerated cabinets
--------	---

### Other accessories

880570	Kit remote alarm
880685	Ethernet connectivity kit IJF for Refrigeration
881298	IoT module for refrigerated cabinets and counters
922432	POE switch

# Accessories

---

## Recommended Detergents

PNC Code	Description
OS2881	S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T
OS2883	S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity
OS2884	S04 GLASSES & HARD SURFACES CLEANERS; 6 BOTTLES X 750ML
OS3257	S05 - MULTIPURPOSE DEGREASER; 6PCS X 750ML; ADR&IMDG Limited Quantity